


## PG Range


(12yr Design Life in Float Service at 20°C)

### Dimensions (mm)



### Standard terminal (mm)

T11 Threaded Insert 8mm Stud



### Physical Specification

Nominal Voltage		12V
Nominal Capacity		130 AH
Dimension	Length	408 ± 2 mm
	Width	177 ± 2 mm
	Container Height	225 ± 2 mm
	Total Height (with Terminal)	225 ± 2 mm
Weight		Approx 37.6kg
Standard Terminal		T11

## PG12V130



### Discharge Characteristics (25°C, 77°F)

Rated Capacity	20hr Rate(1.80v/cell)	128.00AH	Constant Voltage Charge	Cycle	Initial Charging Current Less than 32.0A Voltage 14.4V ~ 15.0V at 25°C (77°F)
	10hr Rate(1.80v/cell)	120.00AH			
	5hr Rate(1.75v/cell)	104.50AH			
	3hr Rate(1.75v/cell)	93.60AH			
Capacity Affected by Temperature	1hr Rate(1.60v/cell)	74.40AH	Standby	Recommended Charge Current less than 32.0A Voltage 13.5V ~ 13.8V at 15°C (77°F)	
	40°C (104°F)	103%			
	25°C (77°F)	100%			
	0°C (32°F)	86%			

### Internal Resistance mΩ

4.0 mΩ

### Constant Current Discharge Characteristics Unit: Amperes (25°C, 77°F)

F.V/Time	10min	15min	20min	30min	45min	1h	2h	3h	4h	5h	6h	8h	10h	20h
1.85V/cell	140.4	118.1	104.8	86.9	67.0	57.4	37.1	27.9	22.9	19.2	16.9	13.5	11.6	6.20
1.80V/cell	160.7	132.6	115.8	94.4	72.3	60.5	39.9	30.0	24.3	20.4	17.9	14.2	12.0	6.42
1.75V/cell	182.5	149.4	128.0	102.5	78.9	66.0	41.5	31.2	25.2	20.9	18.4	14.7	12.3	6.58
1.70V/cell	206.1	165.8	141.3	112.0	85.0	69.8	43.7	32.8	26.3	22.1	19.3	15.3	12.8	6.75
1.65V/cell	221.3	177.5	150.3	118.1	89.9	72.2	45.3	34.2	27.3	22.8	20.0	15.9	13.2	6.96
1.60V/cell	243.5	194.4	163.3	126.1	93.4	74.4	46.5	35.0	27.9	23.3	20.4	16.1	13.4	7.07

### Constant Power Discharge Characteristics Unit:(Watts/cell) (25°C, 77°F)

F.V/Time	10min	15min	20min	30min	45min	1h	2h	3h	4h	5h	6h	8h	10h	20h
1.85V/cell	262.2	222.7	199.6	167.3	130.2	111.8	72.9	55.0	45.2	38.1	33.5	27.0	23.2	12.4
1.80V/cell	296.5	246.7	217.4	179.0	139.4	117.4	77.8	58.7	47.8	40.2	35.3	28.3	24.0	12.8
1.75V/cell	331.4	274.7	238.0	192.9	150.6	127.4	80.6	60.9	49.3	41.0	36.3	29.2	24.6	13.1
1.70V/cell	365.9	300.6	260.8	209.5	161.6	134.4	84.8	63.9	51.4	43.3	38.0	30.4	25.5	13.5
1.65V/cell	389.4	319.4	275.4	219.2	169.5	138.0	87.4	66.2	53.2	44.5	39.2	31.3	26.2	13.9
1.60V/cell	418.7	344.1	295.9	232.3	175.2	141.4	89.2	67.6	54.2	45.5	39.9	31.8	26.7	14.1



Power-Sonic Europe Limited  
 3 Buckingham Square, Wickford, Essex, SS11 8YQ  
 Tel: +44 (0)1268 560686 Fax: +44 (0)1268 560902  
 sales@power-sonic.co.uk  
 www.power-sonic.co.uk